

# Trailers with ISO Container Latches



Total weight	12.000 kg	Net weight appr.	5.300 kg
Length of Platform	9,000 mm	Width of platform	2.440 mm
Length incl. towbar appr.	10.850 mm	Length of towbar	1.850 mm
Height of platform	1.300 mm	Total height (2 Co)	4.360 mm

Container twist lock positions 1050 mm to front end and 1892 mm to rear end.  
2 container bolster with twist-locks acc. to ISO Standards.

Side frame with retractable eyelets every 800 mm

4 RORO lashing rings.

4 brake shoes and holder positioned to each wheel.

4 half sized mudguards.

Tool Box

Spare tire and spare tire holder.

Holder for 4pcs fuel canisters.

NATO-type position light system.

1 extractable stair at rear end, self adjusting steps. Completely plugged in under mowing conditions. 2000 x 1000 mm.

Removable safety handrail stanchions with chain around the free space of platform at rear end. Same system in front of the forward free space of platform.

Single action Jost landing legs with swivel gearbox integrated.



Nordic Shelter AS  
Rosenborgveien 3  
N-1630 Gamle Fredrikstad  
Norway  
[sales@nordicshelter.no](mailto:sales@nordicshelter.no)



For off-road use 4 plywood support plates 500 x 500 x 40 for landing legs.

Platform complete in longitudinal U-profiles with antislip surface.

2 axles 6.000 kg typ ADR with brake drum and parabolic spring.

Two line air pressure brake system. Manual Handbrake.

4 x Tires - Off road- Sand profile- 385/65 R 22,5 Type CONTI TL 160K HSC1

Lights in HELLA design, NATO-type. 2 rear lights, 4 position lamps per side. All necessary functions. 2 x 7 pin plug system.

All steel parts in Desert Tan color RAL 1002

Manual for repair and maintenance.

